



TRIVIEW is a trademark of Tatung Company of America, Inc.

Triview LCD Hand-Held Test Monitor - *NEW!* With Blanview Technology (Sunlight Readable)



Model # TLM-0271

Includes Velcro Wrist Band for Hands-Free Operation

LCD Panel

Screen Size 2.7 inch

Viewable size 54.72mm (H) x 41.04mm(V)

Dot Pitch 0.171mm x 0.171mm

View angle H/V -80°, +80°/-80°, +80°

Contrast ratio 400:1

Brightness 400 cd/m²

Resolution 320 x 240

Response Time 80ms

Display Color 262K

Control key define \ominus , +, Power

Power Supply

Input Voltage 5V_{DC}/1.2A

Consumption <3.2W

Charger Input: 100~240V_{AC}, 0.2A, 50~60Hz; Output: 5V_{DC}/1.2A

Battery 3.7V_{DC}/1200mAh 1-cell Li-ion battery (Embedded inside the monitor)

Video

Input: Composite video, connector: 1 BNC Level: 1.0V_{p-p} / 75 Ω

Output: 1 BNC connector for CVBS loop-through output

OSD: Video Contrast, battery indicator & information

System Compatibility

Scanning Frequency

NTSC : 15750Hz \pm 500Hz / 60Hz, PAL : 15625Hz \pm 500Hz / 50Hz

Charging time* 3.5 hours average

Operating time* Continuously display time: 6 hours average; Standby time: 12+ hours.

RoHS compliant

* The charging and working period will vary correspondence with environment temperature